



## TECHNICAL DATA SHEET

A-9<sup>®</sup> ALUMINUM-CUTTING FLUID**Description:**

Relton's **A-9 Aluminum-Cutting Fluid** is a non-staining oil, formulated for a wide range of applications on non-ferrous metals such as aluminum, magnesium, copper, brass, and bronze. **A-9** is a combination of mineral oil and selected natural esters which are particularly suitable for machining non-ferrous metals where staining from sulfur-containing oils is objectionable.

**Typical Uses:**

- Most machining operations on non-ferrous metals such as aluminum, brass, bronze, copper, and magnesium
- Light-duty drawing for both ferrous and non-ferrous metals

**Typical Inspections:**

API Gravity, @ 60° F:	24.9
Specific Gravity, g/cc, 60° F:	0.905
Pounds per gallon:	7.534
Viscosity @ 40° C, cst:	22.3
Flash Point, COC, ° F:	360
Pour Point, ° C:	-20
VOC:	nil
Active Sulfur, %:	none
Chlorine, %:	none
Copper Corrosion:	nil
Color/form:	light-green/liquid

## Technical Data Sheet -- A-9

---

---

### **Features:**

- Anti-mist agent reduces oil mist in workplace.
- A-9 does not stain non-ferrous brass and bronze components.
- A-9 minimizes tool wear, reduces cutting temperature, and produces excellent surface finishes with moderate cutting speeds and depths.

A-9

2/10/97 Updated: 07/22/05

317 Rolyn Place • Arcadia, CA 91007-2838 / P.O. Box 60019-6019 • Arcadia, CA 91066-6019  
PHONE: (800) 423-1505 • FAX: (626) 446-9671