



API Rotary Drilling connection - External threading

Snap-Tap®



API spec. 7 - 1998



Size	Dimensions in mm		
	IC	L	S
22	12,7	22,0	4,71
27	15,875	27,0	6,15

22ER/27ER



Pitch	Dimensions in mm							Grades					
								Coated			Uncoated		
TPI	PDY	PDX	APICODE	TGTPF	RE	CTF	Designation	CP200	CP300	CP500	H15		
5,0	2,0	2,5	V040	3	0,508	1,016	22ER5API404		■	■			
4,0	1,95	2,55	V038R	2	0,965	1,651	22ER4API386		■	■			
5,0	2,2	3,2	V040	3	0,508	1,016	27ER5API404		■	■			
4,0	2,2	3,2	V038R	3	0,965	1,651	27ER4API384	■	■	■			
4,0	2,2	3,2	V038R	2	0,965	1,651	27ER4API386	■	■	■			
4,0	2,2	3,2	V050	3	0,635	1,27	27ER4API504	■	■	■			
4,0	2,2	3,2	V050	2	0,635	1,27	27ER4API506	■	■	■			

API Rotary Drilling connection - Internal threading



API spec. 7 - 1998

Size	Dimensions in mm		
	IC	L	S
22	12,7	22,0	4,71
27	15,875	27,0	6,15

22NR/27NR



Pitch	Dimensions in mm							Grades					
								Coated			Uncoated		
TPI	PDY	PDX	APICODE	TGTPF	RE	CTF	Designation	CP200	CP300	CP500	H15		
5,0	2,0	2,5	V040	3	0,508	1,016	22NR5API404		■	■			
4,0	1,9	2,5	V038R	2	0,965	1,651	22NR4API386		■	■	■		
5,0	2,2	3,2	V040	3	0,508	1,016	27NR5API404		■	■			
4,0	2,2	3,2	V038R	3	0,965	1,651	27NR4API384	■	■	■			
4,0	2,2	3,2	V038R	2	0,965	1,651	27NR4API386	■	■	■			
4,0	2,2	3,2	V050	3	0,635	1,27	27NR4API504	■	■	■			
4,0	2,2	3,2	V050	2	0,635	1,27	27NR4API506	■	■	■			

■ Stock standard

Subject to change refer to current price- and stock-list