




OK-VISE CLAMPS



| CODE | TYPE | A | | | B | C | D | E | SOCKET HEAD SCREW DIN912 | PRESSING FORCE OF JAWS kN | TIGHTENING TORQUE Nm | WEIGHT IN GRAMS APPROX | HARDNESS OF JAWS HRC |
|------------------------|-----------|-----|---------|-----|----|----|----|-----|-----------------------------------|------------------------------------|----------------------------|---------------------------------|----------------------------|
| | | MIN | OPTIMUM | MAX | | | | | | | | | |
| Serrated Jaws | | | | | | | | | | | | | |
| OKV1000 | BK2-VT | 27 | 29 | 31 | 29 | 15 | 21 | 2.5 | M8x20 | 25 | 44 | 55 | 48-52 |
| OKV1002 | DK2-VT | 42 | 45 | 49 | 41 | 22 | 30 | 4 | M12x30 | 65 | 145 | 180 | 48-52 |
| OKV1004 | FK2-VT | 57 | 61 | 65 | 56 | 29 | 42 | 5 | M16x40 | 110 | 360 | 465 | 48-52 |
| Smooth Jaws | | | | | | | | | | | | | |
| OKV1008 | BK2-VT-S | 27 | 29 | 31 | 29 | 15 | 21 | 2.5 | M8x20 | 25 | 44 | 55 | 48-52 |
| OKV1010 | DK2-VT-S | 42 | 45 | 49 | 41 | 22 | 30 | 4 | M12x30 | 65 | 145 | 180 | 48-52 |
| OKV1012 | FK2-VT-S | 57 | 60 | 64 | 56 | 29 | 42 | 5 | M16x40 | 110 | 360 | 465 | 48-52 |
| Stainless Steel | | | | | | | | | | | | | |
| OKV1020 | BK2-VT-SS | 27 | 29 | 31 | 29 | 15 | 21 | 2.5 | M8x20 | 25 | 44 | 55 | 48-52 |