

USA WATER FITTINGS

They interchange with all major manufacturers systems with origins from the USA. Couplings and nipples are manufactured from brass and suitable for temperatures to 200°C and pressure to 200psi.

Note: Spare seals for 200 series = **HCT5600**, 300 series = **HCT5700** & 500 series = **HCT5800**

Non Valved


| 200 SERIES (1/4" hole) | | 300 SERIES (3/8" hole) | | 500 SERIES (1/2" hole) | |
|---|---|-----------------------------------|-------------|---------------------------|-------------|
| CODE/CAT NO. | HOSE ID | CODE/CAT NO. | HOSE ID | CODE/CAT NO. | HOSE ID |
| Straight Couplings | | | | | |
| HCT1204/204 or TUK1204 | 1/4 | HCT1306/306 | 3/8 | HCT1506/506 | 3/4 |
| CMD1205/205 | 5/16 | HCT1308/308 | 1/2 | | |
| HCT1206/206 or TUK1206 | 3/8 | | | | |
| 45° Couplings | | | | | |
| HCT1224/224 or CMD1224 | 1/4 | HCT1328/328 or CMD1328 | 1/2 | | |
| CMD1225/225 | 5/16 | | | | |
| HCT1226/226 | 3/8 | | | | |
| 90° Couplings | | | | | |
| HCT1214/214 | 1/4 | HCT1318/318 | 1/2 | HCT1516/516 | 3/4 |
| CMD1215/215 | 5/16 | | | | |
| HCT1216/216 | 3/8 | | | | |
| Nipples - Male | | | | | |
| CODE/CAT NO. | PIPE THREAD | CODE/CAT NO. | PIPE THREAD | CODE/CAT NO. | PIPE THREAD |
| HCT8251 | R1/8 | CMD8352 or HCT8352 or RED8352/352 | R1/4 | CMD8554 or HCT8554 | R1/2 |
| HCT8252/252 or CMD8252 | R1/4 | HCT8353/353 | R3/8 | HCT8556/556 | R3/4 |
| HCT8253/253 | R3/8 | HCT8354/354 | R1/2 | | |
| Nipples - Female | | | | | |
| HCT9551 or TUK9551 | G1/8 | | | | |
| HCT9552 | G1/4 | HCT9556/352FB | G1/4 | CMD9560 | R1/2 |
| Extension Nipples | | | | | |
| CODE/CAT NO. | DESCRIPTION | | | | |
| HCT9451*/251 x 100mm | 200 series, G1/8" thread x 100mm long | | | | |
| HCT9452A*/252 x 100mm | 200 series, G1/4" thread x 100mm long | | | | |
| HCT9452B**/251 x 150mm or TUK9452B | 200 series, R1/8" thread x 150mm long | | | | |
| CMD9452A**/252 x 140mm | 200 series, G1/4" thread x 140mm long | | | | |
| HCT9453**/352 x 150mm | 300 series, R1/4" thread x 150mm long | | | | |
| * = Threaded full length below the hex & grooved for easier cutting to length | | | | | |
| ** = Not threaded for full length. | | | | | |
| Straight Couplings - Body only - No barb | | | | | |
| CODE/CAT NO. | DESCRIPTION | | | | |
| HCT1101/200 | Like 204 above but with G1/8" female thread | | | | |
| HCT1102/200 | Like 204 above but with G1/4" female thread | | | | |
| HCT1104/300 | Like 306 above but with G1/4" female thread | | | | |
| HCT1105/300 | Like 306 above but with G3/8" female thread | | | | |
| Connectors | | | | | |
| CODE/CAT NO. | DESCRIPTION | | | | |
| HCT2006/200-6 | 200 Series for 3/8" ID hose | | | | |
| Valved | | | | | |
| 200 SERIES (1/4" hole) | | 300 SERIES (3/8" hole) | | | |
| CODE/CAT NO. | HOSE ID | CODE/CAT NO. | HOSE ID | | |
| Straight Couplings | | | | | |
| HCT2204/204V | 1/4 | HCT2308/308V | 1/2 | | |
| CMD2205/205V | 5/16 | | | | |
| HCT2206/206V | 3/8 | | | | |
| 45° Couplings | | | | | |
| HCT2224/224V or CMD2224 | 1/4 | HCT2328/328V | | | |
| CMD2225/225V | 5/16 | | | | |
| HCT2226/226V or CMD2226 or TUK2226 | 3/8 | | | | |
| 90° Couplings | | | | | |
| HCT2214/214V or CMD2214 | 1/4 | HCT2318/318V or TUK2318 | 1/2 | | |
| CMD2215/215V | 5/16 | | | | |
| HCT2216/216V or TUK2216 | 3/8 | | | | |
| Valved Nipples | | | | | |
| | PIPE THREAD | PIPE THREAD | | | |
| HCT9252 or TUK9252 | R1/4 | | | | |
| HCT9352 or TUK9352 | R1/4 | | | | |
| HCT9353 | R3/8 | | | | |



HCT1204



HCT1224



HCT1214



HCT8252



HCT9552



HCT9451



HCT1101



HCT2006

